


NOTES:

1. MATERIALS AND FINISHES:
 BODY - BRASS, COLD PLATING
 CONTACT PIN - BERYLLIUM COPPER & BRASS, COLD PLATING
 INSULATOR - PTFE, NATURAL
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
 B. REQUENCY RANGE: 0-18 GHz
 C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS, MIN.
3. MECHANICAL:
 A. DURABILITY: 500 CYCLES MIN.
 B. TEMPERATURE RANGE: -65°C to +165°C



THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
NC	INITIAL RELEASE	18-Jul-02	----	GRS
A	UPDATE DRAWING FORMAT	14-Jul-14	2764	MZ



SCALE 3.000



CUSTOMER OUTLINE DRAWING
 ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm ±0.05mm 0.5 - 6mm ±0.1mm 6 - 30mm ±0.2mm 30 - 120mm ±0.3mm ANGLES ±1° NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	MATERIAL	DRAWN M. ZHANG	DATE 14-Jul-14	TITLE SMA R/A PANEL JACK EXTENDED TEFLON/CONTACT (.0"/.224")		Amphenol Connex	
	REFERENCE SMA6552E1-004-3GT5GP-50	ENGINEER S. DUAN	DATE 14-Jul-14				
	CONFIGURATION LEVEL: In Work	APPROVED S. HSIEH	DATE 14-Jul-14	SHEET 3 OF 3	ITEM NO.		
	FINISH	CAD FILE	SCALE: 6.0:1.0	REV A	PART NO. 132318-13		