REV.	DATE	DESCRIPTION
NC	12/09/07	INITIAL RELEASE
A	01/08/08	REVISE BARREL O.D AND FERRULE LENGTH, I.D. AND O.D.



	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5	FERRULE	COPPER	NEXCOTE	1
4	CAP	BRASS	NEXCOTE	1
3	CONTACT PIN	BRASS	SILVER	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY/NUT	BRASS	NEXCOTE	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	01/08/08
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/172/172176–11.DWG

Amphenol Connex

PART DESCRIPTION
N R/A PLUG
FOR LMR400/B9913, HEX NUT.

PART NO. 172176–11

DWG. NO.	REV.	SIZE	SCALE
172176–11.DWG	A	A	NA