



IP67 SMA CABLE ASSEMBLIES

Pre-Configured 50 Ohm Assemblies on Flexible Cables

Ordering Information

IP67 SMA Cable Assemblies on RG-316

Part Number	Description
095-902-569-XXXX	IP67 SMA Straight Plug to SMA Straight Bulkhead Jack, RG-316
095-902-570-XXXX	IP67 SMA Right Angle Plug to SMA Straight Bulkhead Jack, RG-316

Note: 'XXXX' denotes length code. See available lengths in chart below.

Standard Lengths Available

Length Code	Length in Inches (Millimeters)
-006	6.00 in (152.40 mm)
-012	12.00 in (304.80 mm)
-018	18.00 in (457.20 mm)
-024	24.00 in (610 mm)
-036	36.00 in (914.40 mm)
-M025	9.84 in (250 mm)
-M050	19.69 in (500 mm)
-M075	29.53 in (750 mm)
-M100	39.37 in (1000 mm)

Overview

Amphenol RF offers a variety of pre-configured IP-rated SMA cable assemblies designed on flexible RG-316 coax cable. These 50 ohm assemblies are available in straight or right-angle plug to straight bulkhead jack configurations and provide reliable electrical performance up to 3 GHz. SMA cable assemblies are ideal for applications that require a more ruggedized, waterproof solution such as industrial and IoT equipment.

IP67 SMA cable assemblies are designed with lightweight, durable connectors that feature a threaded coupling mechanism for secure locking and vibration resistance. The flexibility of the cable, along with the small diameter, makes them suitable for a variety of indoor and outdoor applications.

Features and Benefits

- Engineered with flexible RG-316 cable type
- Available in a variety of standard lengths
- Supports both indoor and outdoor applications
- Vibration resistant design

Applications

- Industrial Equipment
- Antennas
- Outdoor Kiosks
- Base Stations
- Military Communications

Amphenol RF

Four Old Newtown Road
Danbury, CT 06810

For more information visit www.amphenolrf.com
or call 800.627.7100

Amphenol® RF

Technical Specifications

Electrical

Impedance	50Ω
Frequency Range	DC - 3 GHz
Dielectric Withstanding Voltage	750 VRMS Max

Environmental

Temperature Range	-65°C to +165°C
RoHS Compliance	Compliant with Exemption 6C

Mechanical

Mating Cycles	500 Min
Coupling Mechanism	Threaded

Materials

Body	Brass, Gold Plating
Contact	Beryllium Copper, Gold Plating
Insulator	PBT

Note: Technical specifications are typical and may vary by specific part number. Please see component drawing.

Amphenol RF

Four Old Newtown
Road Danbury, CT

86810

For more information visit www.amphenolrf.com

or call 800.627.7100