



NOTES:

1. MATERIALS AND FINISHES:
 MMCX STR PLUG - BRASS, GOLD PLATING
 SMA STR BHD JACK IP 67 - BRASS, GOLD PLATING
 CABLE - RG 316
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
3. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 "AMPHENOL RF, 95-900-597-XXX AND DATE CODE"

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	15-DEC-25	17687	KRK



LENGTH TABLE		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH "L" IN INCHES [METERS]
95-900-597-003	-	3.00 [0.076]
95-900-597-004	-	4.00 [0.102]
95-900-597-005	-	5.00 [0.127]
95-900-597-006	-	6.00 [0.152]
95-900-597-007	-	7.00 [0.178]
95-900-597-008	-	8.00 [0.203]
95-900-597-009	-	9.00 [0.229]
95-900-597-010	-	10.00 [0.254]
95-900-597-011	-	11.00 [0.279]
95-900-597-012	-	12.00 [0.305]
95-900-597-018	-	18.00 [0.457]
95-900-597-024	-	24.00 [0.610]
95-900-597-036	-	36.00 [0.914]
-	95-900-597M100	39.37 [1.000]
95-900-597-048	-	48.00 [1.219]

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.99" [0 - 0.609]	±0.25" [0.006]
24.00" - 59.99" [0.610 - 1.523]	±0.50" [0.013]
5.0' - 24.99' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

FREQUENCY: DC - 6 GHz CONTINUITY

VSWR: _____ 1 MAX. HI-POT: 300 VRMS

INS. LOSS: _____ dB MAX. OTHER

CUSTOMER OUTLINE DRAWING
 ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE: <0.5mm = ±0.05mm [-0.020 = ±0.002] 0.5 - 6mm = ±0.1mm [-0.020 - 0.236 = ±0.004] >6.00 - 30mm = ±0.2mm [-0.236 - 1.181 = ±0.008] >30.00 - 120mm = ±0.3mm [-1.181 - 4.725 = ±0.012]		MATERIAL SEE NOTES		TITLE MMCX STR PLUG TO SMA STR BHD JACK IP 67 USING RG 316 CABLE		Amphenol RF	
THIRD ANGLE PROJ. REFERENCE		ANGLES = ±1°		ENGR.1 RANISH ENGR.2 DATE 09-OCT-25		SHEET NO. 2 OF 2 SCALE: 2.6:1.0		SIZE B DRAWING NO. 95-900-597-XXX REV A ITEM NO. 95-900-597-XXX PART NO. 95-900-597-XXX	