

I. MATERIALS AND FINISHES:	
BODY	- BRASS, NICKEL PLATING
CONTACT	- BRASS, GOLD PLATING
INSULATOR	- PEEK, NATURAL
RETAINING RING	- BRASS, NICKEL PLATING
WASHER	- BRASS, NICKEL PLATING
SHELL	- ZINC ALLOY, NICKEL PLATING
GASKET	- RUBBER, RED
SPRING	- BERYLLIUM COPPER, NICKEL PLATING

3. MECHANICAL:
A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -40°C TO +85°C

4. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: PACKAGING TO BE MARKED
"AMPHENOL RF, 31-7096, AND DATE CODE"

"AMPHENOL"
TYP (2)

SCALE 2.000



NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp., (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE:

<0.5mm = ±0.05mm	<0.020 = ±0.002
0.5 - 6mm = ±0.1mm	>0.020 - 0.236 = ±0.004
>6.0 - 30mm = ±0.2mm	>0.236 - 1.181 = ±0.008
>30.0 - 120mm = ±0.3mm	[1.181 - 4.725 = ±0.012]

MATERIAL
SEE NOTES

TITLE
PFAS-FREE BNC MALE
TO BNC MALE ADAPTER

Amphenol RF

5	4	3	2	1
---	---	---	---	---