	135106-01-XX.XX	REVI	SIONS
NOTES:	DRAWING NO.	EV DESCRIPTION	DATE ECO APPR
1. PACKAGE CABLE ASSEMBLY IN BAG. TAG IN BAG WITH "AMPHENOL CONNEX, 135106-01-XX.XX AND DATE CODE".	THIRD ANGLE PROJ. 🕀 🖯	A RELEASE TO MFG.	05-Apr-12 MG
2. CABLE ASSEMBLY TO BE 100% TESTED FOR HI-POT, CONTINUITY, SHORTS AND OPEN.			
			SCALE 0.500
L a	ENGTH (SEE TABLE)		
	INGTH (SEE TABLE)		
$\begin{array}{c c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & &$			(3)
			<i>i</i>
—			
■ 0.75″ MAX — ■			
[19.50 MM]			
PART	NUMBER LENGTH		
135106-	-01-06.00 6"±0.15		
	-01-12.00 12"±0.15		
	-01-24.00 24"±0.25		
	-01-36.00 36″±0.50		
DECIEN PROJUPEMENTS			
DESIGN REQUIREMENTS:			
FREQUENCY TO GHz X CONTINUITY			
			HEAT SHRINK THRE
		009-954-341 A/R 4 132114 1 3	HEAT SHRINK TUBE SMA CRIMP PLUG
VSWR : 1 MAX X HI-POT : 500 VRMS		132114 1 3 009-881-205 A/R 2	SMA CRIMP PLUG RG-316 CABLE
		132114 1 3 009-881-205 A/R 2 132117 1 1	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK
VSWR : 1 MAX X HI-POT : 500 VRMS		132114 1 3 009-881-205 A/R 2	SMA CRIMP PLUG RG-316 CABLE
UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: MATERIAL	DRAWN DATE	132114 1 3 009-881-205 A/R 2 132117 1 1 PART NUMBER QTY ITEM	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK DESCRIPTION FINISH
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1° ANGLES 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	GOPI M 05-Apr-	132114	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK DESCRIPTION FINISH
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1° ANGLES 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	GOPI M O5-Apr-	132114	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK DESCRIPTION FINISH
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1° ANGLES 4.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	GOPI M O5-Apr-	132114	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL 4.015 (0,381 mm) 4.005 (0,127 mm) 4 1°	GOPI M O5-Apr- ENGINEER DATE GOPI M O5-Apr-	132114	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK DESCRIPTION FINISH
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL 4.015 (0,381 mm) 3 PLACE DECIMAL 4.005 (0,127 mm) NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or	GOPI M O5-Apr- ENGINEER DATE GOPI M O5-Apr-	132114	SMA CRIMP PLUG RG-316 CABLE SMA CRIMP JACK DESCRIPTION FINISH Amphenol Connex SCALE: 2.5:1 SHEET LOF L