

NOTES:

1. MATERIALS AND FINISHES:
 FERRULE - COPPER, NICKEL PLATING
 HEX NUT - BRASS, NICKEL PLATING
 LOCK WASHER - BRASS, NICKEL PLATING
 BODY - BRASS, NICKEL PLATING
 CONTACT - PHOSPHOR BRONZE, GOLD PLATING
 GASKET - SILICONE RUBBER, RED
 INSULATOR - PTFE, NATURAL

2. ELECTRICAL:
 A. IMPEDANCE: 50 OHMS
 B. FREQUENCY RANGE: DC - 11 GHz
 C. DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS, MIN.

3. MECHANICAL:
 A. DURABILITY: 500 CYCLES MIN.
 B. TEMPERATURE RANGE: -65°C TO +165°C

4. CRIMPED FERRULE HEX CRIMP SIZE .213"


5. CRIMPED CONTACT PIN HEX CRIMP SIZE .100" OR SOLDER.

6. MAX. PANEL THICKNESS = 6.5 [.256]



THIRD ANGLE PROJ. ☺

REVISIONS



REV	DESCRIPTION	DATE	ECN	APPR
A	RELEASE TO MFG.	09-May-01	44187	SH
B	THE LOCK WASHER WAS CHANGED\RD-DMI2010403F	13-Jun-12	48832	SH
C	THE BARREL & CONTACT WERE CHANGED\RD-DM12071101M	16-Aug-12	49194	SH
D	SYNC & ADDED THE P/N	12-Aug-19	12522	SH



RECOMMENDED CABLE STRIPPING DIM'S



RECOMMENDED MOUNTING HOLE

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:
 <0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES
 ± 0.05mm ± 0.1mm ± 0.2mm ± 0.3mm ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL SEE NOTES	DRAWN M.ZHANG ENGINEER F.WANG REFERENCE EAR# REF: N6421AI-NT3G-142AU-50 CONFIGURATION LEVEL: In Work	DATE 09-Aug-19 DATE 21-Mar-19 APPROVED S.HSIEH DATE 09-Aug-19	TITLE N BULKHEAD CRIMP JACK (FOR RG-142A/U CABLE) SCALE: 2.5:1.0 SHEET 2 OF 2	Amphenol RF www.amphenolrf.com
FINISH	CAD FILE	DWG SIZE B	REV D	DRAWING NO. N6421AI-NT3G-142AU-50SAP ITEM NO. 036421AAA02NA5A PART NO. 82-5373-RFX