


REV.	DATE	ECR NO.	DESCRIPTION
NC	07/18/13	XXXXXX	INITIAL RELEASE




1. IMPEDANCE: 50 OHM
2. FREQUENCY RANGE: 0-18 GHZ
3. VSWR: 1.3 MAX.
4. INSERTION LOSS: 0.3 dB, MAX.
5. DIELECTRIC WITHSTANDING VOLTAGE: 750 VRMS, MIN.
6. DURABILITY: 500 CYCLES MIN.
7. TEMPERATURE RANGE: -65°C TO +125°C
8. CONTACT PIN TO SOLDER


7	COVER	STAINLESS STEEL	GOLD	1
6	BODY	STAINLESS STEEL	GOLD	1
5	INSULATOR	PTFE	NATURAL	1
4	CONTACT PIN	BRASS	GOLD	1
3	RETAINING RING	SUS 304	NATURAL	1
2	GASKET	SILICONE RUBBER	RED	1
1	COUPLING NUT	STAINLESS STEEL	PASSIVATED	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 6mm ± 0.10mm 6 - 30mm ± 0.20mm 30 - 120mm ± 0.30mm ANGLES ± 1° UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: <.020 ± 0.002" .020 - .236 ± 0.004" .236 - 1.180 ± 0.007" 1.180 - 4.724 ± 0.012" ANGLES ± 1° DO NOT SCALE DRAWING
--

APPROVALS	DATE
DRAWN M.ZHANG	07/18/13
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE C:/CONNEX/132111SS-10.DWG	



RECOMMENDED
CABLE STRIPPING DIM'S



Amphenol Connex

PART DESCRIPTION
SMA R/A DIRECT SOLDER PLUG (FOR TFLEX-405 CABLE)
PART NO.
132111SS-10
DWG. NO.
132111SS-10.DWG
REV.
NC
SIZE
A
SCALE
NA