NOTES:

I. MATERIALS AND FINISHES:
BODIES - BRASS, NICKEL PLATED
CONTACT - BERYLLIUM COPPER, GOLD PLATED

INSULATOR - PTFE

GLASS SEAL - KOVAR STEEL , GOLD PLATING

2. ELECTRICAL: A. IMPEDANCE: 50 OHM

B. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.

A. DURABILITY: 500 CYCLES MIN.

B. TEMPERATURE RANGE: -65° C TO 165° C


C. SOLDER JOINT MUST WITHSTAND A LEAKAGE RATE OF I X  $10^{-5}$  cc/sec OF TRACER GAS AT ATMOSPHERIC PRESSURE.

4. PACKAGING:


A. QUANTITY: SINGLE PACK

B. MARKING: PACKAGING TO BE MARKED


"AMPHENOL RF, 31-6789, AND DATE CODE"







SCALE 2.000



## **CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

<0.5mm	0.5 - 6mm	6 - 30mm	30 - 120mm	ANGLES
± 0.05mm	$\pm$ 0.lmm	$\pm 0.2$ mm	± 0.3mm	±Ι°
NOTICE - These	e drawings, specif	ications, or othe	r data (I) are, ar	d remain the
			upon request; and	
			on other than thos	
			hese drawings, spe	
			rson to anyone for	
			n any manner licer	
			rson to manufactur rwise, that may in	
			ications, or other	
1014104 10 01	anderosea by said	aramings, specia	rearrons, or orner	www.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:

MATERIAL	DRAWN	DATE	T
	S.DUAN	26 - May - 17	
- -	ENGINEER	DATE	
REFERENCE	B.WYMAN	07 - Apr - 17	
EAR# 7620	APPROVED	DATE	
EXP#	K.CAPOZZI	02 - Jun - 17	S
CONFIGURATION LEVEL: In Work	CAD FILE		
FINISH			

THIRD ANGLE PROJ. 🕀 🖯

TITLE
TNC JACK,
FRONT MOUNT WITH
HERMETIC RECEPTACLE
SCALE: 5.0:1.0 SHEET 2 OF 2
DWG SIZE REV
В В

	Amphenol RF
_	www.amphenolrf.com
-	DRAWING NO. 31-6789
	ITEM NO. 31-6789
	PART NO. 31-6789