NOTES:	THIRD ANGLE PROJ. 🕀 🚭		
NOTES;		REV	DESCRI
I. MATERIALS AND FINISHES: INNER CONDUCTOR - BRASS OUTER CONDUCTOR - BRASS NUT - BRASS INSULATOR - PTFE, NATURAL O-RING - SILICONE RUBBER, RED			RELEASE
2. ELECTRICAL: A. IMPEDANCE: 50 OHM B. FREQUENCY RANGE: DC - 3 GHz C. VSWR: I.IO MAX. D. INSERTION LOSS: .I MAX. E. DWV: IO00VRMS F. INTERMODULATION: \leq -165 dBc (2 X 43 dBm) G. INSULATION RESISTANCE: 5000 m Ω H. CONTACT RESISTANCE: OUTER CONDUCTOR <1.5 m Ω INNER CONDUCTOR <1.0 m Ω	20.5		
 MECHANICAL: A. DURABILITY: 500 CYCLES MIN. B. TEMPERATURE RANGE: -40° C TO +85° C C. COMPATIBLE WITH ALL STANDARD 4.3/10 PLUGS 4. ENVIRONMENTAL: 			
A. PLUG MEETS IP-67 STANDARD IN MATED CONDITION.			
5. ASSEMBLY SPEC. 349-50926			
6. CONTACT/INSULATOR ASSEMBLY TO BE SHIPPED LOOSE IN BAG.		4]
7. PACKAGING: A. QUANTITY: SINGLE PACK B. MARKING: BAG TO BE MARKED "AMPHENOL RF, 431-124P-52S, AND DATE CODE"	22 ON HEX		
			CONTAC



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: < 0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES $\pm 0.05mm$ $\pm 0.1mm$ $\pm 0.2mm$ $\pm 0.3mm$ $\pm 1^{\circ}$	MATERIAL BRASS	DRAWN K. ELMES	DATE 09-Mar-16	TITLE - 4.3/10SM
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they		ENGINEER K. ELMES	DATE 09-Mar-16	FOR 0.250"
are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any	REFERENCE EAR #6645	APPROVED K. CAPOZZI	DATE 10/21/16	SEMI-RIGID CA
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	CONFIGURATION LEVEL:	CAD FILE		DWGSIZĖ
	FINISH			В

PTION	VISIONS	DATE	ECO	APPR
TO MFG.		10/21/16	02202	KCE
	\square	Mr.		
		/ ///)		
		VV		
/INSULA	FOR ASSEMBLY			
		DRAV	VING)
	JTLINE			
	UTLINE RE FOR INTERNA			
	RE FOR INTERNA	L USE ONLY	RF	
	re for interna Amp	henol		
	re for interna Amp www.	henolrf.	com	
heets a	RE FOR INTERNA Amp www. DRAWING NO.	h e n o amphenolrf. 431-124P-	com	
	re for interna Amp www.	h e n o l amphenolrf. 431-124P- -124P-52S	com	