


NOTES:

1. MATERIALS AND FINISHES:
BODY – BRASS, NICKEL PLATING
CONTACT – BRASS, GOLD PLATING
INSULATOR – PTFE, NATURAL
2. ELECTRICAL:
A. IMPEDANCE: 75 OHM
B. FREQUENCY RANGE: DC 0–4 GHz
C. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.
3. MECHANICAL:
A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: –65°C to +165°C
4. SOLDER CONTACT TO CABLE
WHEN CRIMPING CONTACT PIN TO CABLE, CRIMP WITH AMPHENOL TOOL 227–944 (M22520/5–01) AND DIE SET 227–1221–100, CAVITY 'B'
5. WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL TOOL 277–944 (M22520/5–01) AND DIE SET 227–1221–100 CAVITY 'A'
6. USE WITH TIMES FIBER 2240V OR OTHER RG59 QUAD SHIELD OR HEAD END CABLES.




THIRD ANGLE PROJ. 

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A2	SEE SHEET 1	29–Oct–02	--	TONY
A3	SEE SHEET 1	15–Apr–03	--	TONY
A4	SEE SHEET 1	30–Jun–05	41899	SH
B	SEE SHEET 1	27–Jul–05	--	SH
B1	SEE SHEET 1	16–Aug–05	--	SH
C	SEE SHEET 1	27–Feb–08	--	AW
D	SEE SHEET 1	23–Mar–10	47967	SH
E	NOTE 4 WAS CHANGED\RD–10121301F	27–Dec–10	48342	SH



RECOMMENDED
CABLE STRIPPING DIM'S



CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:
<0.5mm ±0.05mm 0.5 – 6mm ±0.1mm 6 – 30mm ±0.2mm 30 – 120mm ±0.3mm ANGLES ±1°

NOTICE – These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

REFERENCE

FINISH

DRAWN

F.WANG

ENGINEER

S.LI

APPROVED

S.HSIEH

CAD FILE

F:\DWG\CNPD\31\71066–ESZ

DATE

17–Dec–10

DATE

17–Dec–10

DATE

17–Dec–10

TITLE

BNC PLUG (75 OHM)
(FOR RG–59/U QUAD
SHIELD CABLE)

SCALE: 3/1

DWG SIZE

B

CODE ID

74868

REV

E

Amphenol RF

Danbury CT USA, Tainan Taiwan, Shenzhen China
www.amphenolrf.com

DRAWING NO. 31–71066

ITEM NO. 31–71066

PART NO. 31–71066