REV.	DATE	DESCRIPTION
NC	09/16/03	INITIAL RELEASE



NOTES:

1. CRIMPED FERRULE
   HEX CRIMP SIZE .429"
2. CONTACT PIN TO SOLDER

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5				
4	FERRULE	COPPER	SILVER	1
3	CONTACT PIN	BER. COPPER	SILVER	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	BRASS	SILVER	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	09/16/03
CHECKED		
ISSUED		
SHEET	1 OF 1	
CAD FILE	C:/272/272106HEX.DWG	

Amphenol Connex

PART DESCRIPTION: 7/16 CRIMP PLUG WITH HEX NUT (FOR RG-214/U CABLE)

PART NO. 272106HEX

DWG. NO.	REV.	SIZE	SCALE
272106HEX.DWG	A	A	NA