REV.	DATE	DESCRIPTION
NC	07/31/02	INITIAL RELEASE



CRIMP NOTES:

1. CRIMPED FERRULE HEX CRIMP SIZE .187"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .068"
3. MAX. PANEL THICKNESS = 3.2mm

8	FERRULE	BRASS	NICKEL
7	SLEEVE	DELRIN	NATURAL
6	BARREL	BRASS	NICKEL
5	HEX NUT	BRASS	NICKEL
4	LOCK WASHER	BRASS	NICKEL
3	CONTACT PIN	BER. COPPER	GOLD
2	INSULATOR	TEFLON	NATURAL
1	BODY	BRASS	NICKEL
	DESCRIPTION	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS

DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERANCE ONLY

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.XXX = ± 0.005"
.XX = ± 0.010"
.X = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	07/31/02
CHECKED		
ISSUED		

Amphenol - Connex
CONNECTOR CORPORATION

TITLE: MINI-UHF BULKHEAD CRIMP JACK (FOR RG-316/U DOUBLE BRAIDED CABLE)

SIZE	FSCM NO.	DWG. NO.	REV.
A	99001	182331.DWG	NC
SCALE NA	PART NO. 182331	SHEET 1 OF 1	