REV.	DATE	DESCRIPTION
NC	05/01/06	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S











NOTE:

1. CRIMPED FERRULE
   HEX. CRIMP SIZE .178"
2. CRIMPED CONTACT PIN
   HEX. CRIMP SIZE .068"

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5	FERRULE	BRASS	NICKEL	1
4	SLEEVE	DELRIN	NATURAL	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	05/01/06
CHECKED		
ISSUED		
SHEET	1 OF 1	

CAD FILE C:/182/182126.DWG

Amphenol Connex

PART DESCRIPTION
MINI–UHF CRIMP PLUG
(RG–316/U DOUBLE BRAID CABLE)

PART NO. 182126

DWG. NO.	REV.	SIZE	SCALE
182126.DWG	NC	A	NA