REV.	DATE	DESCRIPTION
NC	05/27/02	INITIAL RELEASE





RECOMMENDED MOUNTING HOLE DIMENSIONS



RECOMMENDED CABLE STRIPPING DIM'S

CRIMP NOTES:

1. CRIMPED FERRULE HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .118"
3. MAX PANEL THICKNESS = 6.5mm

8			
7	FERRULE	COPPER	NICKEL
6	CONTACT PIN	BRASS	GOLD
5	HEX NUT	BRASS	NICKEL
4	LOCK WASHER	BRASS	NICKEL
3	GASKET	GASKET	RED
2	INSULATOR	TEFLON	NATURAL
1	BODY	BRASS	NICKEL
	DESCRIPTION	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS

DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERANCE ONLY

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.XXX = ± 0.005"
.XX = ± 0.010"
.X = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	05/27/02
CHECKED	
ISSUED	

Amphenol - Connex
CONNECTOR CORPORATION

TITLE
N REVERSE POLARITY BULKHEAD CRIMP JACK
(FOR BELDEN 8214, 9913, 9914, LMR 400 CABLE)

SIZE	FSCM NO.	DWG. NO.	REV.
A	99001	172220RP.DWG	NC

SCALE	PART NO.	SHEET
NA	172220RP	1 OF 1