REV.	DATE	ECR NO.	DESCRIPTION
NC	09/23/08	100053	INITIAL RELEASE
A	10/30/08	–	REVISE BARREL LENGTH (17.40 / 12.65)



NOTES:

1) CRIMPED FERRULE HEX CRIMP SIZE .255" [6.48]
2) CONTACT PIN TO SOLDER.

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5	FERRULE	COPPER	GOLD	1
4	COVER	BRASS	GOLD	1
3	CONTACT PIN	BER. COPPER	GOLD	1
2	INSULATOR	PTFE	NATURAL	1
1	BODY	BRASS	GOLD	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	GRS	10/30/08
CHECKED		
ISSUED		
SHEET	1 OF 1	

CAD FILE C:/142/142344.DWG

Amphenol Connex

PART DESCRIPTION
SMZ R/A SNAP LOCK CRIMP PLUG
(FOR 734A CABLE)

PART NO. 142344

DWG. NO.	REV.	SIZE	SCALE
142344.DWG	A	A	NA