	142201 75	DEVICTORS	
NOTES:		REVISIONS DESCRIPTION	DATE ECO APPR
1. INSULATOR (ITEM NO.2) MUST WITHSTAND A 6 LBS. MIN	THIRD ANGLE PROJ. \varTheta 🖯 A	RELEASE TO MFG.	27-Apr-11 HR
PUSHOUT FORCE FROM BODY(ITEM NO.1) AFTER STAKING OPERATION			
2. NOTE 1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING BODY( ITEM NO. 1)			
0.610"			
[I5.50] MM			
			_//// <i> ////////////////////////////////</i>
- 0.437"			
0.250" HEX			SCALE 4.000
(6.35) MM [5.80] MM			
0.189"			
[4.80] MM			Ø0.038
			[0.96] MM
		✓ 0.020 [0.51] MM	0.016
		<u> </u>	[0.40] MM
	Ø 0.126" [3.20] MM	<del> </del>	
		I	1
		0.386 — [9.80] MM	-
	Ø 0.088" [2.24] MM		
	FORMING MIN.		
STAKE IN 4 PLACES————————————————————————————————————			
— 0.059" ← (SEE NOTE1,2) [1.50] MM	0.250" ON HEX		
10-32UNF-2A-	[6.35] MM		
<del>  -</del> 0.125" <del></del>			
Ø 0.200" — [3.20] MM	0.171" ON FLAT [4.35] MM		
[5.10] MM			
[2.00] MM			
- $        -$			ASS GOLD 1  ASS GOLD 1
		5 CONTACT PIN BR	PASS GOLD 1
			PASS GOLD 1 FLON NATURAL 1
RECOMMENDED RECOMMENDED CAR	BLE		FLON NATURAL 1
STRIPPING DIMENSIO			ASS GOLD 1
		NO. DESCRIPTION MAT	ERIAL FINISH QTY
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:  2 PLACE DECIMAL  3 PLACE DECIMAL  ANGLES  SEF TABLE  HADI D	DATE TITL		
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°		MINI 75 OHM SMB BHD	Amphenol
property of Amphenol Corp. (2) must be returned upon request; and (3) are	27-Anr-11	SOLDER JACK FOR	Connex
confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is	ED DATE (	0.085″,0.086″CABLE	1
other data by Amphenol Corp., or to any other person to anyone for any purpose is TASK-622		\$0	CALE: 4.0:1 SHEET I OF I
or to be regarded by implication or otherwise in any manner licensing, granting captures and the second of the sec	I F	DWG SIZE DRAWING NO.	REV