



REV.	DATE	ECR NO.	DESCRIPTION
NC	09/20/10	XXXXXX	INITIAL RELEASE





TOP VIEW



BOTTOM VIEW

RECOMMENDED PCB LAYOUT



7				1
6				1
5				1
4				1
3	CONTACT PIN	BERYLLIUM COPPER	GOLD	1
2	INSULATOR	PTFE	NATURAL	1
1	BODY	BRASS	GOLD	1
DESCRIPTION	MATERIAL	FINISH	QTY	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.40mm 30 - 120mm ± 0.50mm
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 - .315 = ± 0.007" .315 - 1.180 = ± 0.015" 1.180 - 4.724 = ± 0.020"
DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN M.ZHANG	09/23/10
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE C:/CONNEX/132410.DWG	

Amphenol Connex			
PART DESCRIPTION SMA END LAUNCH RECEPT. JACK (FOR .047" THICK PCB)			
PART NO. 132410			
DWG. NO. 132410.DWG	REV. NC	SIZE A	SCALE NA