REV.	DATE	ECR NO.	DESCRIPTION
NC	01/15/10	XXXXXX	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S



NOTES:
1. CRIMP BODY OVER INNER FERRULE USING .105" HEX.
2. CONTACT PIN TO SOLDER

	DESCRIPTION	MATERIAL	FINISH	QTY
9	INNER FERRULE	BRASS	GLOD	1
8	SLEEVE	BRASS	GLOD	1
7	INSULATOR	PTFE	NATURAL	1
6	CONTACT	BRASS	GLOD	1
5	COUPLING NUT	BRASS	GLOD	1
4	RETAINING RING	SUS 304	NATURAL	1
3	GASKET	SILICONE	RED	1
2	INSULATOR	PTFE	NATURAL	1
1	BODY	BRASS	GLOD	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	M.ZHANG	01/15/10
CHECKED		
ISSUED		
SHEET	1 OF 1	

CAD FILE C:/CONNEX/132393.DWG

Amphenol Connex

PART DESCRIPTION
SMA PLUG
(FOR 1.13mm CABLE)

PART NO. 132393

DWG. NO. 132393.DWG | REV. NC | SIZE A | SCALE NA