REV.	DATE	DESCRIPTION
NC	01/22/03	INITIAL RELEASE
A	01/04/06	UPDATE BODY MATERIAL TO STAINLESS STEEL



RECOMMENDED
MOUNTING HOLE



8				
7				
6				
5	HEX NUT	BRASS	NICKEL	1
4	LOCK WASHER	BRASS	NICKEL	1
3	CONTACT PIN	BER. COPPER	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	STAINLESS STEEL	PASSIVATED S.S.	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	01/04/06
CHECKED		
ISSUED		
SHEET	1 OF 1	
CAD FILE	C:/132/132170SS.DWG	

Amphenol Connex

PART DESCRIPTION
SMA BULKHEAD FEMALE TO FEMALE ADAPTER

PART NO. 132170SS

DWG. NO.	REV.	SIZE	SCALE
132170SS.DWG	A	A	NA