REV.	DATE	DESCRIPTION
NC	02/12/01	INITIAL RELEASE



RECOMMENDED CABLE STRIPPING DIMENSIONS



RECOMMENDED MOUNTING HOLE











CRIMP NOTES:

1. CRIMPED CONTACT PIN HEX CRIMP SIZE .068"
2. MAX. PANEL THICKNESS = 8mm

	DESCRIPTION	MATERIAL	FINISH
1	BODY	BRASS	NICKEL
2	BARREL	BRASS	GOLD
3	CONTACT PIN	PHOS. BRONZE	GOLD
4	INSULATOR	TEFLON	NATURAL
5	LOCK WASHER	BRASS	NICKEL
6	HEX NUT	BRASS	NICKEL
7			
8			

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS

DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERANCE ONLY

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5–6 = ± 0.2
6–30 = ± 0.4
30–120 = ± 0.6
120–315 = ± 1
315–1000 = ± 1.6
1000–2000 = ± 2.4

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	02/12/01
CHECKED		
ISSUED		

Connector Corporation

TITLE: TNC BULKHEAD FRONT MOUNT DIRECT 75ohm (FOR .085", .086" CABLE)

SIZE	FSCM NO.	DWG. NO	REV.
A	99001	122463.DWG	NC

SCALE	PART NO.	SHEET
NA	122463	1 OF 1