REV.	DATE	ECR NO.	DESCRIPTION
NC	03/27/09	–	INITIAL RELEASE





RECOMMENDED
MOUNTING HOLE



RECOMMENDED
CABLE STRIPPING DIM'S

NOTES:

1. CRIMPED FERRULE HEX CRIMP SIZE .429" [10.89]
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .118" [4.57]
3. MAX. PANEL THICKNESS = 3.5mm

8				
7	FERRULE	COPPER	NICKEL	1
6	HEX NUT	BRASS	NICKEL	1
5	LOCK WASHER	BRASS	NICKEL	1
4	GASKET	RUBBER	RED	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	PTFE	NATURAL	1
1	BODY	BRASS	NICKEL	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	GRS	03/27/09
CHECKED		
ISSUED		
SHEET	1 OF 1	

CAD FILE C:/122/122405RP.DWG

Amphenol Connex

PART DESCRIPTION
TNC REVERSE POLARITY BULKHEAD
CRIMP JACK (FOR BELDEN 9913, 9914)

PART NO. 122405RP

DWG. NO.	REV.	SIZE	SCALE
122405RP.DWG	NC	A	NA