


REV.	DATE	ECR NO.	DESCRIPTION
NC	07/06/09	-	INITIAL RELEASE



- NOTES:
1. CRIMPED FERRULE
HEX CRIMP SIZE .105"
 2. SOLDER CENTER CONTACT

11	INNER FERRULE	BRASS	NICKEL	1
10	NUT	BRASS	NICKEL	1
9	BARREL	BRASS	NICKEL	1
8	CONTACT PIN	BRASS	GOLD	1
7	WASHER	BRASS	NICKEL	1
6	SPRING	SK5	NICKEL	1
5	RETAINER RING	BRASS	NICKEL	1
4	GASKET	RUBBER	RED	1
3	INSULATOR	PTFE	NATURAL	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.40mm 30 - 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 - .315 = ± 0.007" .315 - 1.180 = ± 0.015" 1.180 - 4.724 = ± 0.020"	APPROVALS	DATE	Amphenol Connex		
	DRAWN J.CHENG	07/06/09			
	CHECKED		PART DESCRIPTION		
	ISSUED		BNC R/A CRIMP PLUG (FOR 1.32 MM CABLE)		
	SHEET 1 OF 1				
			PART NO.		
			112752		
CAD FILE			DWG. NO.	112752.DWG	REV. NC
C:/CONNEX/112752.DWG			SIZE	A	SCALE NA