NOTES:

1. MATERIALS AND FINISHES:
   BODY, HEX NUT AND LOCK WASHER - BRASS, NICKEL PLATING
   CONTACT - BeCu, GOLD PLATING
   BULLET CONTACT - BRASS, GOLD PLATING
   INSULATOR - PTFE, NATURAL
   O-RING AND GASKET - SILICONE RUBBER, RED
   FERRULE - COPPER, NICKEL PLATING

2. ELECTRICAL:
   A. IMPEDANCE: 50 OHM
   B. FREQUENCY RANGE: DC - 9 GHz
   C. VSWR: 1.30 MAX. @ DC - 3 GHz
            1.40 MAX. @ 3 - 6 GHz
            1.50 MAX. @ 6 - 9 GHz
   D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.

3. MECHANICAL:
   A. DURABILITY: 500 CYCLES MIN.
   B. TEMPERATURE RANGE: -65°C TO +165°C
   C. SEALING MEETS IP-67 REQUIREMENTS IN UMNATED CONDITION

4. PACKAGING:
   A. QUANTITY: SINGLE PACK
   B. MARKING: PACKAGING TO BE MARKED
      "AMPHENOL RF, 31-7011 AND DATE CODE"
   C. GASKET, LOCK WASHER, HEX NUT, BULLET CONTACT AND
      FERRULE ARE PACKAGED LOOSE.

5. CABLE ASSEMBLY INSTRUCTIONS:
   A. TRIM CABLE AS SHOWN.
   B. SLIDE FERRULE ONTO CABLE.
   C. SOLDER CABLE CENTER CONDUCTOR TO BULLET CONTACT.
   D. INSERT CABLE WITH FOIL ENTERING CONNECTOR AND
      BRAID OVER KNURL.
   E. CRIMP FERRULE OVER BRAID WITH 0.105" HEX.

6. SHOWS CABLE ENTRY DIMENSIONS.

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	16-NOV-23	16821	SH



SCALE 1.500



RECOMMENDED MOUNTING HOLE DIMENSIONS



RECOMMENDED CABLE STRIPPING DIMENSIONS



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.

REFERENCE	EAR#
	10560

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:

<0.5mm = ±0.05mm	[<0.020 = ±0.002]
>0.5 - 6mm = ±0.1mm	[>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm	[>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm	[>1.181 - 4.725 = ±0.012]

ANGLES = ±1°

MATERIAL: SEE NOTES

ENGR.1	ENGR.2	DATE
SASI D	JACK LIANG	28-APR-21

TITLE: RP TNC STR BHD JACK FRONT MOUNT IP 67 FOR RG 178 CABLE

SHEET NO. 2 OF 2 | SCALE: 6.0:1.0

Amphenol RF

SIZE	DRAWING NO.	REV
B	31-7011	A
	ITEM NO. 31-7011	
	PART NO. 31-7011	